

Model: DS-49PCT

49" Intel based Signage with PCT Touch







Features:

- Full HD (1920 x 1080) LED Panel with PTC Touch for good multimedia experience.
- Made of tempered glass, providing panel protection and enhances vivid graphics.
- All metal housing ensures a long life and protects sign from scratches.

Specification		
Model	DS-49PCT	
Panel Parameter	Panel Size	49"
	Active Area	1073.6mm(W) × 804.4mm(H)
	Brightness	350nits
	Max. Resolution	1920*1080
	Contrast Ratio	4000:1
	Panel Life	50000 hours
	Responsive Time	7ms
	Viewing Angle	H178/V178
Power Supply	AC 110V-240V, 50HZ/60HZ	
Touch Screen	Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness: 7H Operation system: DOS; Windows XP / 7 / 8.1 / 10 / 11; Linux	

NORCO S.E.A. PTE LTD GST Registration No.: 200901437Z Tel: (65) 6853 0809

Fax: (65) 6853 0153

Company Registration No.: 200901437Z

20 Woodlands Link, #09-23, Woodlands East Ind' Estate, Singapore 738733

Website: www.sg-norco.com



Applications	Supermarket, Hotel, Mall center, Shop, Commercial buildings etc.		
Certificate Approval	CE, RoHS, FCC, ISO9001		
Warranty	12 months		
Features	Security and password protection, anti-thief design		
	Set up time on/off		
	Support Remote controller		
	Support Safety lock system		
	Support Media Format	MPEG1/2/4, AVI, RM, WMV, DAT, JPEG, BMP, PPT, WORD, EXCEL, TXT, MP3, RMVB, SWF etc.	
	Temperature	Storage: -20 Celsius degree to 60 Celsius degree	
		Working: -10 Celsius degree to 50 Celsius degree	
	Fixing Method	Wall mount	
Available solutions :			
Windows Version	i5 cpu, 4G/8G RAM,128G/256G SSD, integrated GPU, wifi, RJ45 supported Intel i5, dual core, frequency 2.5Ghz, turbo 3.1Ghz DDR3, I/O: DC12V+HDMI+VGA+2*USB3.0+2*USB2.0+LAN+2*AUDIO i7 cpu, 4G/8G RAM,128G/256G SSD, integrated GPU, wifi, RJ45 supported		
	Intel i7 cpu, dual core, frequency 2.9ghz, turbo 3.6Ghz DDR3, I/O: DC12V+HDMI+VGA+2*USB3.0+2*USB2.0+LAN+2*AUDIO		